

Technical Manual



01.005.01

**REMOVE AND INSTALL
FRONT FENDER**

STARK FUTURE



SAFETY WARNINGS

Observe your local health and safety guidelines. Ensure a safe working environment. Wear appropriate protective gear. Deviating from the prescribed order may result in injury or damage to the products.



TOOLS

TRX 30



OPERATION TIME

2 Minutes

REMOVAL



WARNING

Before proceeding with any work on the bike, make sure it is turned off and the charger disconnected.

- 1 Unscrew all 4 front fender bolts.



NOTE

Beware of falling bolts or bushings.

- 2 Carefully take the front fender out between the forks.

3

INSTALLATION



WARNING

Before proceeding with any work on the bike, make sure it is turned off and the charger disconnected.

- 1 Carefully fit the front fender between the forks.
- 2 Align the front fender holes with the front number plate studs and the triple clamp.
- 3 Tighten at least one bolt with a bushing to secure the fender in place.
- 4 Tighten the remaining bolts with bushings by hand until all hold in place.
- 5 Tighten all front fender bolts to **8 Nm**.

starkfuture.com

ENG 2023-06

Copyright © 2023 Stark Future SL. All rights reserved.
Reproduction, even in part, as well as copying of all kinds,
is permitted only with the express written permission
of the copyright owner.

STARK FUTURE