

Technical Manual



02.010.01

**REMOVE AND INSTALL
FRONT BRAKE PADS**

STARK FUTURE



SAFETY WARNINGS

Observe your local health and safety guidelines. Ensure a safe working environment. Wear appropriate protective gear. Deviating from the prescribed order may result in injury or damage to the products.



TOOLS

- TRX 45
- ALN 10
- Pliers
- Flat screw driver



CONSUMABLES

Brake cleaner



OPERATION TIME

20 Minutes

REMOVAL



WARNING

Before proceeding with any work on the bike, make sure it is turned off and the charger disconnected.

- 1 Remove the front brake caliper.
Refer to:



02.005.01

[Remove and Install front brake caliper ↗.](#)

- 2 Remove the front brake pads safety clips.
- 3 Remove the front brake pads pin.
- 4 Remove the front brake pads.

INSTALLATION



WARNING

Before proceeding with any work on the bike, make sure it is turned off and the charger disconnected.

- 1 Clean the brake pads backplate.



NOTE

Avoid contaminating the brake pads braking surface.

- 2 Install brake pads.



NOTE

Ensure the brake pads ferodo is facing the inside.

- 3 Insert the brake pads pin.

4

- 4 Install the front brake pads clips.
- 5 Install the front brake caliper. Refer to:



02.005.01

Remove and Install front brake caliper ↗.



WARNING

Check brakes operation before operating the bike.

starkfuture.com

ENG 2023-06

Copyright © 2023 Stark Future SL. All rights reserved.
Reproduction, even in part, as well as copying of all kinds,
is permitted only with the express written permission
of the copyright owner.

STARK FUTURE