

Technical Manual



03.011.01

REMOVE AND INSTALL CHAIN

STARK FUTURE



SAFETY WARNINGS

Observe your local health and safety guidelines. Ensure a safe working environment. Wear appropriate protective gear. Deviating from the prescribed order may result in injury or damage to the products.



TOOLS

Chain breaker



CONSUMABLES

Master link



OPERATION TIME

10 Minutes

REMOVAL



WARNING

Before proceeding with any work on the bike, make sure it is turned off and the charger disconnected.

- 1 Rotate the rear wheel to place the master link on the lower side of the swingarm and halfway between the front and rear sprockets.



NOTE

Take care not to trap your fingers.

- 2 Select an appropriate sized adapter for the chain. Chain specifications can be found in the Owners Manual.
- 3 Remove the master link using the chain breaker.
- 4 Slowly pull the chain just below the front sprocket.



NOTE

Take care not to damage the swingarm as the chain clears the rear sprocket.

INSTALLATION



WARNING

Before proceeding with any work on the bike, make sure it is turned off and the charger disconnected.

- 1 Run the chain through the chain guide and around the rear sprocket.



NOTE

Take care not to trap your fingers.

- 2 Run the chain around the front sprocket until both ends meet at the bottom of the swingarm.
- 3 Insert the master link from the wheel side onto both ends of the chain.
- 4 Use a chain breaker with a flat tip to press the master link plate.
- 5 Use a riveting tip to press both master link pins.



NOTE

The rivet diameter expansion should not exceed **5.5 mm + 0.1/0**.

starkfuture.com

ENG 2023-07

Copyright © 2023 Stark Future SL. All rights reserved.
Reproduction, even in part, as well as copying of all kinds,
is permitted only with the express written permission
of the copyright owner.

STARK FUTURE