

Technical Manual



**05.041.01**

**REMOVE AND INSTALL  
SKID PLATE**

**STARK FUTURE**



## SAFETY WARNINGS

Observe your local health and safety guidelines. Ensure a safe working environment. Wear appropriate protective gear. Deviating from the prescribed order may result in injury or damage to the products.



## TOOLS

TRX 45



## OPERATION TIME

8 Minutes

# REMOVAL

---



## WARNING

Before proceeding with any work on the bike, make sure it is turned off and the charger disconnected.



## NOTE

- Rest the bike on the side stand, if equipped.
- If not equipped with side stand, request the help from a second person to hold the bike.

- 1 Unscrew the skid plate bolts, 1x on each side and 2x at the rear underneath.
- 2 Push the skid plate downwards.

# INSTALLATION

---



## WARNING

Before proceeding with any work on the bike, make sure it is turned off and the charger disconnected.



## NOTE

- Rest the bike on the side stand, if equipped.
  - If not equipped with side stand, request the help from a second person to hold the bike.
- 
- 1 Push the skid plate into place until the holes are aligned.
  - 2 Tighten the bolts to **15 Nm**.

starkfuture.com

ENG 2023-06

Copyright © 2023 Stark Future SL. All rights reserved.  
Reproduction, even in part, as well as copying of all kinds,  
is permitted only with the express written permission  
of the copyright owner.

**STARK FUTURE**