

Technical Manual



06.010.01

**REMOVE AND INSTALL
CONTROL SWITCH**

STARK FUTURE



SAFETY WARNINGS

Observe your local health and safety guidelines. Ensure a safe working environment. Wear appropriate protective gear. Deviating from the prescribed order may result in injury or damage to the products.



TOOLS

- TRX 30
- TRX 20



OPERATION TIME

10 Minutes

REMOVAL



WARNING

Before proceeding with any work on the bike, make sure it is turned off and the charger disconnected.

- 1 Disconnect the handlebar controls.
Refer to:



06.030.07

Disconnect and reconnect handlebar controls ↗.

- 2 Remove the control switch wiring rubber strap.
- 3 Carefully pull the wiring out of the triple clamp routing channel.



NOTE

If you feel excessive resistance when pulling the wiring out of the triple clamp, please check that you disconnected the correct plug or the wiring is not stuck.

- 4 Hold the switch and untighten the control switch clamp bolt.



NOTE

Beware of falling objects.

- 5 Remove the control switch.

INSTALLATION



WARNING

Before proceeding with any work on the bike, make sure it is turned off and the charger disconnected.


- 1 Hold the control switch in place on the handlebar.



NOTE

The buttons should be facing towards the rear of the bike with the ON/OFF button towards the inner side.

- 2 Tighten the control switch clamp bolt to **3 Nm**.
- 3 Fit the cable through the triple clamp routing channel.
- 4 Connect the handlebar controls.
Refer to:



06.030.07

Disconnect and reconnect handlebar controls ↗.

- 5 Fit the control switch wiring rubber strap to secure it to the handlebar.



WARNING

Turn on the bike and connect to the Stark phone to check battery status and that the bike is operating normally after disconnecting electronic components.

starkfuture.com

ENG 2023-08

Copyright © 2023 Stark Future SL. All rights reserved.
Reproduction, even in part, as well as copying of all kinds,
is permitted only with the express written permission
of the copyright owner.

STARK FUTURE